

BITUMINOUS MARKER ADHESIVE

Code: PE-BITU

True leaders do not follow
...they lead the way



WHAT IS THE BITUMINOUS MARKER ADHESIVE?

- High-performance adhesive.
- Highly reliable and safe to handle.
- Excellent adhesion and cohesion.
- Quick and easy application.
- Fast drying.
- High impact resistance.
- Top-quality compounds.
- Suitable for use on asphalt concrete and Portland cement concrete.

Application Quick Guide

1. The pavement surface must be free of dust, grease, and completely dry.
 2. Unpack the adhesive and pour it into a metal container, estimating the approximate volume to be used.
 3. Heat the product to a controlled temperature and stir until it reaches a semi-liquid consistency.
 4. Apply the adhesive directly to the prepared area, as well as a light layer to the surface of the accessory. Gently press it into place. Allow the adhesive to cool before exposing it to traffic.
 5. Use the adhesive in a well-ventilated area. Avoid smoking during the application process.
- Wear gloves and protective goggles to prevent burns.

Note:

- Store the adhesive in its original packaging in a cool, dry place until use.
- Ensure the adhesive is applied to completely dry surfaces.
- In case of staining on the pavement, it can be removed with common biodegradable cleaners.
- If the adhesive comes into contact with skin, clean it with plenty of water and common biodegradable cleaners.

Technical Specifications

* Softening point (ASTM D-36):	210° F
* Penetration point 77° F (ASTM D-5)(dmm):	10-20
* Viscosity 400° F, CPS:	2000-6000
* Fluidity (ASTM D-3407) inch:	None
* Melting point (ASTM D-92) C.O.C.:	500° F
* Minimum room temperature application conditions:	
* Application temperature:	40°F
* Do not heat the product near:	395° F- 415° F
* Drying time:	435° F
	3-5 minutes, depending on room temperature