

LIGHTEN ARROW TRAILER

CODE: RE-FLE-SOL

Images are mere illustrative models .



Leader don't follow steps
... marks the way

FEATURES:

Luminic and flashing signalisation manufactured out in a dye galvanized sheet box cal.16 with anti-corrosion coating and finished in black acrylic enamel.

Cluster led based illumination board in amber or red colors with intelligent control for display strong luminic signal patterns in different timing sequences or flashing modes.

Metallic body made out in Hollow Structural Tube 4"x2" for operate in deviations, work zones, slopes, emergency events or reparation works. Its strong support on wheels (rhine 14") and reinforced axis offers an easy handle for any task.

The lighten trailer has all what is needed for an optimal operation on any terrain, including a central Jack for equilibrate the device in leaning grounds. Traffic lights, directional lights and flashers and lights connectors harness.

Solar powered by a photovoltaic panel and rechargeable batteries 60W-12V-40AH.

TECHNICAL DATA:


TRAILER

- * Manufactured out in: Hollow Quadrangular Tube (HQT) 2.5" galvanized HQT 1.5"; Angle 1 1/4" x 1/8" galvanized dye sheet 4" x 8" cal.16.
- * Color: Traffic yellow.
- * Measure: Trailer 94,48 x 102,36 in. Height:140 in.
- * Suspension: Springs
- * Support : 1,500 lbs. axis
- * Winch: 1,800 lbs.

LIGHTEN BOARD

- * Manufactured out in: HQT 4" x 2" galvanized dye sheet cal.18.
- * Total weight: 198,41 LBS.
- * Powered: 12 Volts.
- * Led Clusters: 25.
- * Leds life expectancy term 10 years.

Flashing templates



Lighten Arrow Board

