

# Vitemflex® Trailer-mounted Attenuator

Code: REV-1000

A leader doesn't follow steps, **he marks the way.**

## FEATURES

- A trailer-mounted attenuator for utility service trucks.
- Made of Vitemflex®
  - Length: 16 ft 3.66 in.
  - Width: 7 ft 10 in.
  - Height: 7 ft 6 in.
- It works as a crash cushion.
- It includes two axles that bear up to 7,000 lb. and a 7 ft 10 in. platform.
- Four 15" rims with four lug nuts.
- Four 15" rim all-terrain tires.
- Four packages of 13/4" 4-leaf springs.
- Axle spindles for the trailer brake controller.
- Male-female connectors for the trailer brake controller.
- Plastic water tank with a capacity of 1000 L (264 US gal).
- Structural reinforcements with two inlets and two outlets with caps on the sides of 1 ½.
- Medium-density polyethylene striped bumper reinforced with polyurethane.
- It includes a flashing arrow sign on the platform.
- A container with a capacity of 1,800 L (475 US gal) of garbage.
- Two rear lights for stop and reverse.
- Additional RHS green supports on the sides for the bumper.
- Spare tire.
- Trailer coupler, 3" welded chassis for tow ball with a capacity of 12,500 lb.

